

Glossy

Masonry hydro-enamel certified for environments with food presence.



Ideal for plants where food is processed

Excellent covering power

High adhesion

Resistance to abrasion

Very low VOC

Transpiring

Super washable

MAIN AREAS OF USE

It is particularly suitable to

Paint surfaces that need a waterproof finish, stain resistant, with enamel effect. Particularly suitable for premises where food is processed (kitchens, butchers, etc.) or environments subject to frequent sanitation and washing.

Recommended applications:

Painting surfaces of all kinds: Commercial and residential buildings, showrooms, homes, etc. Suitable substrates (indoor only):

- Lime-based civil finishes
- Cement base civil finishes
- Gypsum (after application of a primer in case of smoothing with very low absorption)
- Plasterboard
- Surfaces already painted, after carefully checking and cleaning the substrate
- Concrete

Standard version: can be coloured according to the **licatacolore2.0** colour fan.

CHARACTERISTICS

Conforms to UNI 11021:2002 is ideal for environments subject to high hygiene/sanitary standards

Excellent touch-up: allows you to correct specific areas without creating halos or discrepancies.

Waterproof and anti-mould, the biocidal additive makes it immune to phytotrophic attacks.

Excellent yield, thanks to the careful selection of raw materials.

Conforms to **UNI EN 13300**.

Available in three versions: **glossy, satin and matt**.

METHODS OF APPLICATION

Preparation of the substrate

The substrate must be clean, flat, cohesive and free of any kind of release agent.

It is always recommended to use a primer to even out the absorption, which becomes mandatory for very absorbent substrates (plaster, plasterboard, etc.).

- **New substrates:** no precautions beyond those indicated
- **Deteriorated or crumbling substrates:** Remove any friable, poorly cohesive or detachable parts and restore the correct flatness with **licata** products.
- **Substrates with poor flatness:** apply the filler **Uniformante LG** before application.
- **Substrates with algae or mould:** pre-treat the affected surfaces with **Sanus** biocide.

Preparation of the product

The product can be diluted with clean water as follows: Brush or roller application: first hand 25% - second hand 20% - Airless application: 25%. After dilution, homogenise the product for a few minutes with a mixer at low speed.

Application

1_Spread the product in two or more cross layers, with a brush, roller or with an Airless machine, taking care to cover 100% of the surface to be treated.

2_In case of multiple applications, paint the next layers spaced by about 3-4 hours.

PRODUCT INFORMATION

| | |
|--|---|
| Appearance | White liquid |
| Yield | 7 – 8 m ² /L in two coats |
| Dilution | First coat 10% Second coat 10% |
| Drying time | Dry to the touch about 3-4 hours Completely dry about 24 hours |
| Application temperature | between +5 °C and + 35 °C and R.H. 70% |
| Storage in unopened original packaging | 12 months in a dry place between +5° and +35°C |
| Packaging | Polypropylene bucket 4 L - 14 L |
| Binding agent | Synthetic copolymers |
| Specific gravity | 1.30 kg/L |
| Covering power | Excellent |
| Dirt pick-up | Low |
| Brightness | Polished, Satin and Opaque |
| Particle size | < 100 microns |
| VOC (Directive 2004/42/EC) for wall paint internal (Cat A/a): | < 100g/L of VOC |

WARNINGS

- Product for professional use.

In the case of applications other than those indicated in the sheet, it is advisable to carry out a suitability check in advance and/or contact the Licata Technical Service for further information.

- Always check the colour, texture and appearance before application. Any claims regarding this will not be accepted once the product has been applied.
 - Do not apply in extreme conditions such as on icy surfaces or in the presence of fog/excessive ambient humidity.
- To avoid aesthetic and functional defects, adequate shielding must be provided in case of direct exposure to sunlight.
- Make sure that the ambient, substrate and product temperatures during application and drying are between +5°C and +35°C.
 - Properly care for the product until it is completely dry and at least in the first 48-72 hours, protecting it from rain, wind, weather and direct sunlight.
 - The temperature and humidity can accelerate (if high) or slow down (if too low) even drastically the maturation process, until it stops completely.
 - The presence of scaffolding, the use of natural raw materials and the impossibility of controlling atmospheric conditions and the substrate can lead to signs of recovery and inhomogeneity for which Licata SpA is not responsible.
 - The fresh product can be washed with water.

SAFETY

Protect eyes and hands during application.

Read and keep the latest version of the Safety Data Sheet available for information on the correct disposal, storage and handling of the product.

NOTES

This data sheet replaces and voids all previous versions.

The instructions and performance information given in this document are based on our current technical-scientific knowledge and must in any case be considered purely indicative and refer to standard laboratory conditions. The purchaser must, therefore, check that the product is suitable for his specific requirements. All the documentation necessary for the safe use of Licata SpA products is available in its most up-to-date form on the **Licata SpA** company website. Additionally, our technical-commercial network guarantees a quick inquiry and remains available to you for information and explanations. For further information, contact the Licata Technical Service at servizio-tecnico@licataspa.it

Data sheet ref.: TDS P10359 - rev.08/21.