#### ΕN

## Licata S.p.A.

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 1 / 14

Replaced revision:1 (Dated 14/01/2025)

### **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

#### SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: P113752
Product name Sesia

UFI: X7S0-P05X-U002-6G2E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Washable siloxane anti-mold water-based paint

1.3. Details of the supplier of the safety data sheet

Name Licata S.p.A. Full address Via dei Mille 32

District and Country 00185 Roma (RM)

Italia

Tel. +39 0922 856088 Fax +39 0922 831427

e-mail address of the competent person

responsible for the Safety Data Sheet controllo-qualita@licataspa.it

1.4. Emergency telephone number

For urgent inquiries refer to NHS111in England: 111

NHS24in Scotland: 111

NHS Direct in Wales: 111 or 0845 4647

In an emergency, if the patient has collapsed or is not breathing properly, call 999

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin sensitization, category 1A H317 May cause an allergic skin reaction.

Hazardous to the aquatic environment, chronic H412 Harmful to aquatic life with long lasting effects.

toxicity, category 3

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

**H317** May cause an allergic skin reaction.

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 2 / 14

Replaced revision:1 (Dated 14/01/2025)

#### SECTION 2. Hazards identification .../>>

**H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

**P280** Wear protective gloves.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

**P273** Avoid release to the environment.

Contains: 2-OCTYL-2H-ISOTHIAZOL-3-ONE

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND

2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

#### **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

CALCINED KAOLIN-CAOLINO CALCINATO

INDEX  $8 \le x < 9$  Substance with a community workplace exposure limit.

EC 296-473-8 CAS 92704-41-1

3-iodo-2-propinilbutilcarbammato

INDEX 616-212-00-7 0,039  $\leq$  x < 0,042 Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1 H372, Eye Dam. 1 H318,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410

M=1

EC 259-627-5 ATE Oral: 500 mg/kg, ATE Inhalation mists/powders: 0,501 mg/l

CAS 55406-53-6 **2-OCTYL-2H-ISOTHIAZOL-3-ONE** 

INDEX 613-112-00-5 0,0015 ≤ x < 0,0025 Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1 H314,

Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100,

Aquatic Chronic 1 H410 M=100, EUH071

EC 247-761-7 Skin Sens. 1A H317: ≥ 0,0015%

CAS 26530-20-1 LD50 Oral: 125 mg/kg, LD50 Dermal: 311 mg/kg, ATE Inhalation

mists/powders: 0,051 mg/l

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

INDEX 613-167-00-5 0,0015  $\leq$  x < 0,0025 Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C

H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100,

Aquatic Chronic 1 H410 M=100, EUH071, Classification note according to

Annex VI to the CLP Regulation: B

EC 611-341-5 Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06% - < 0,6%, Skin Sens.

1A H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,06% - <

0,6%

CAS 55965-84-9 LD50 Oral: 64 mg/kg, LD50 Dermal: 87,12 mg/kg, LC50 Inhalation

mists/powders: 0,33 mg/l/4h

REACH Reg. 01-2120764691-48

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 3 / 14

Replaced revision:1 (Dated 14/01/2025)

#### SECTION 4. First aid measures .../>>

minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice / attention.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

#### **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb

P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 4 / 14 Replaced revision:1 (Dated 14/01/2025)

#### **SECTION 6. Accidental release measures**

the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

#### **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

#### **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und B	AT-Werte-Liste 2022 Ständige Senatskommission zur
-----	-------------	-----------------------------------	---

Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

**TLV-ACGIH ACGIH 2023** 

			3-iodo-2-propi	nilbutilcarbar	nmato					
Predicted no-effect cor	ncentration	- PNEC								
Normal value in fresh	n water					0,5	mg/l			
Normal value in marine water 0,046 mg/l										
Normal value for fresh water sediment 0,017 mg/kg/d										
Normal value for marine water sediment 0,0016 mg/kg/d										
Normal value for water, intermittent release 0,53 mg/l										
Normal value for fresh water, intermittent release 0,53 mg/l										
Normal value of STP	microorgani	sms				0,44	mg/l			
Normal value for the	terrestrial co	mpartment				0,005	mg/kg/d			
Health - Derived no-eff	ect level - D	NEL / DMEL								
	Effects or	n consumers			Effects on w	orkers				
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic		
	local	systemic	local	systemic	local	systemic	local	systemic		
Inhalation					1,16	0,07	1,16	0,023		
					mg/m3	mg/m3	mg/m3	mg/m3		
Skin								2		
								mg/kg		
								bw/d		

## Licata S.p.A. P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 5 / 14 Replaced revision:1 (Dated 14/01/2025)

#### **SECTION 8. Exposure controls/personal protection**

2-OCTYL-2H-ISOTHIAZOL-3-ONE									
nit Value									
Country	TWA/8h		STEL/15min		Remarks / Observ	/ations			
	mg/m3	ppm	mg/m3	ppm					
DEU	0,05		0,1		INHAL				
DEU	0,05		0,1		SKIN				
DEU	0,05		0,1		INHAL				
DEU	0,05		0,1		SKIN				
effect concentra	ation - PNEC								
ie in fresh water					0,0022	mg/l			
ie in marine wate	er				0,22	mg/l			
e for fresh water	sediment				0,0475	mg/kg/d			
ie for marine wat	ter sediment	0,00475	mg/kg/d						
ie for water, inter	0,00122	mg/l							
Normal value for fresh water, intermittent release 0,122 mg/l									
Normal value for the terrestrial compartment 0,0082 mg/kg/d									
	DEU DEU DEU DEU DEU effect concentrate in fresh water in marine water ie for marine water for water, interie for fresh water ie for fresh water ie for fresh water ie for fresh water ie for fresh water in fresh water	Country TWA/8h mg/m3 DEU 0,05 DEU 0,05 DEU 0,05 DEU 0,05 DEU 0,05 effect concentration - PNEC te in fresh water te for fresh water sediment te for marine water sediment te for water, intermittent release te for fresh water, intermittent r	Country TWA/8h mg/m3 ppm DEU 0,05 DEU offect concentration - PNEC The in fresh water The for fresh water sediment The for water, intermittent release The for fresh water, intermittent release The for fresh water, intermittent release	Note	Country TWA/8h STEL/15min mg/m3 ppm mg/m3 ppm  DEU 0,05 0,1 DEU 0ffect concentration - PNEC  The in fresh water sediment the for marine water sediment the for water, intermittent release the for fresh water, intermittent release	Nit Value           Country         TWA/8h         STEL/15min         Remarks / Observation           mg/m3         ppm         mg/m3         ppm           DEU         0,05         0,1         INHAL           DEU         0,05         0,1         INHAL           DEU         0,05         0,1         INHAL           DEU         0,05         0,1         SKIN           Seffect concentration - PNEC           se in fresh water         0,0022           se in marine water         0,22           se for fresh water sediment         0,0475           se for marine water sediment         0,00475           se for water, intermittent release         0,00122           se for fresh water, intermittent release         0,122			

REACTION	MASS OF	5-CHLORO-2-	METHY	2H-ISOTI	HIAZOL-3-ON	E AND 2-M	IETHYL-2H	-ISOTHIAZ	OL-3-ONE	
(3:1	)									
Threshold Limit Val	ue									
Туре	Country	TWA/8h			STEL/15min		Remark	s / Observa	ations	
		mg/m3	ppm		mg/m3	ppm				
MAK	DEU	0,2			0,4		INHAL			
Predicted no-effect	concentra	tion - PNEC								
Normal value in fr	esh water							0,00339	mg/l	
Normal value for f	fresh water	sediment						0,027	mg/kg	
Normal value for r	marine wate	er sediment						0,027	mg/kg	
Normal value of S	TP microor	ganisms						0,23	mg/l	
Normal value for t	the terrestri	al compartmen	t					0,01	mg/kg	
Health - Derived no-	-effect leve	I - DNEL / DM	EL							
	Effec	ts on consume	rs			Effect	s on worker	s		
Route of exposure	e Acute	e Acute		Chronic	Chronic	Acute		Acute	Chronic	Chronic
	local	system	nic	local	systemic	local		systemic	local	systemic
Inhalation								0,04 mg/m3		0,02 mg/m3

			CALCIN	NED KAOL	IN-CAOLINO	CALCINA	TO			
Threshold Limit \	Value									
Type	Country	TWA/8h			STEL/15min		Remar	ks / Observa	itions	
	•	mg/m3	ppm		mg/m3	ppm				
OEL	EU	15					SKIN	polvere tota	ale	
TLV-ACGIH		2					RESP	Polvere		
Predicted no-effe	ect concentra	ation - PNEC								
Normal value in	n fresh water							4,1	mg/l	
Normal value in	n marine wate	er						0,41	mg/l	
Normal value for	or water, inter	mittent release						25	mg/l	
Normal value of	of STP microo	rganisms						1400	mg/l	
Health - Derived	no-effect lev	el - DNEL / DME	L							
	Effe	cts on consumer	S			Effec	cts on worke	rs		
Route of expos	sure Acu	te Acute		Chronic	Chronic	Acut	е	Acute	Chronic	Chronic
	loca	l systemi	С	local	systemic	local		systemic	local	systemic
Inhalation						3		3	3	3
						mg/r	n3	mg/m3	mg/m3	mg/m3

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

## Licata S.p.A. P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 6 / 14 Replaced revision:1 (Dated 14/01/2025)

#### SECTION 8. Exposure controls/personal protection ..../>

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

#### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

#### **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	white	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
рН	8,8	
Kinematic viscosity	not available	
Dynamic viscosity	18000	Method:Brookfield
		Temperature: 20 °C
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,49	
Relative vapour density	not available	
Particle characteristics	not applicable	

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 0,06 % - 0,90 g/litre

P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 7 / 14

Replaced revision:1 (Dated 14/01/2025)

#### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

**CALCIUM CARBONATE** 

Decomposes at temperatures above 800°C/1472°F.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

CALCIUM CARBONATE Incompatible with: acids.

#### 10.6. Hazardous decomposition products

**CALCIUM CARBONATE** 

May develop: calcium oxides, carbon oxides.

#### **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

3-iodo-2-propinilbutilcarbammato

 LD50 (Dermal):
 2000 mg/kg Rabbit

 LD50 (Oral):
 1056 mg/kg Rat

 LC50 (Inhalation vapours):
 670 mg/l Rat

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 8 / 14

Page n. 8 / 14 Replaced revision:1 (Dated 14/01/2025)

#### **SECTION 11. Toxicological information** .../>>

Ossirano, 2-metil-,polimero con ossirano,etere con 1,2,3 propanetriolo (3:1) LD50 (Dermal): > 5 mg/kg Coniglio LD50 (Oral): > 10 mg/kg Ratto

TALC

 LD50 (Dermal):
 2000 mg/kg Rat

 LD50 (Oral):
 5000 mg/kg Rat

 LC50 (Inhalation mists/powders):
 2,1 mg/l Rat

TITANIUM DIOXIDE

 LD50 (Dermal):
 > 10000 mg/kg Coniglio

 LD50 (Oral):
 > 5000 mg/kg Ratto

 LC50 (Inhalation vapours):
 > 6,82 mg/l/4h Ratto

2-OCTYL-2H-ISOTHIAZOL-3-ONE

 LD50 (Dermal):
 311 mg/kg

 LD50 (Oral):
 125 mg/kg Rat

 LC50 (Inhalation mists/powders):
 270 mg/l/4h Rat

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LD50 (Dermal): 87,12 mg/kg Rabbit LD50 (Oral): 64 mg/kg Rat LC50 (Inhalation mists/powders): 0,33 mg/l/4h Rat

**CALCIUM CARBONATE** 

 LD50 (Dermal):
 2000 mg/kg Rat

 LD50 (Oral):
 2000 mg/kg Rat

 LC50 (Inhalation mists/powders):
 3 mg/l Rat

CALCINED KAOLIN-CAOLINO CALCINATO

 LD50 (Dermal):
 5000 mg/kg Rat

 LD50 (Oral):
 5000 mg/kg Rat

 LC50 (Inhalation mists/powders):
 2,07 mg/l/4h Rat

MINEMA 1-2-44

LD50 (Oral): > 5000 mg/kg Ratto

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

#### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### TALC

Overall IARC evaluation: Perineal use of talc-based body powder is possibly carcinogenic to humans (Group2B). Inhaled talc not containing asbestos or asbestiform fibres is not classifiable as to its carcinogenicity (Group 3).

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 9 / 14

Replaced revision:1 (Dated 14/01/2025)

#### SECTION 11. Toxicological information .../>>

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

#### **SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

#### 12.1. Toxicity

3-iodo-2-propinilbutilcarbammato

 LC50 - for Fish
 0,2385 mg/l/96h

 EC50 - for Crustacea
 0,16 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 0,053 mg/l/72h

 EC10 for Algae / Aquatic Plants
 0,0046 mg/l/72h

 Chronic NOEC for Fish
 0,0945 mg/l

 Chronic NOEC for Crustacea
 0,076 mg/l

 Chronic NOEC for Algae / Aquatic Plants
 0,0046 mg/l

TALC

 LC50 - for Fish
 99790,5 mg/l/96h

 EC50 - for Crustacea
 36812 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 7203 mg/l/72h

 EC10 for Algae / Aquatic Plants
 918,089 mg/l/72h

 Chronic NOEC for Algae / Aquatic Plants
 918,089 mg/l

TITANIUM DIOXIDE

LC50 - for Fish > 1000 mg/l/96h

EC50 - for Crustacea > 1000 mg/l/48h Pulce d'acqua grande EC50 - for Algae / Aquatic Plants > 10000 mg/l/72h Alghe cloroficee

EC10 for Algae / Aquatic Plants 12,7 mg/l/72h Chronic NOEC for Algae / Aquatic Plants 5600 mg/l

2-OCTYL-2H-ISOTHIAZOL-3-ONE

 LC50 - for Fish
 0,122 mg/l/96h

 EC50 - for Crustacea
 0,181 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 0,15 mg/l/72h

 EC10 for Algae / Aquatic Plants
 0,068 mg/l/72h

 Chronic NOEC for Algae / Aquatic Plants
 0,068 mg/l

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LC50 - for Fish 0,19 mg/l/96h

EC50 - for Crustacea 0,16 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 0,037 mg/l/72h

Chronic NOEC for Fish 0,0464 mg/l Danio rerio

Chronic NOEC for Crustacea 0,1 mg/l Daphnia magna

Chronic NOEC for Algae / Aquatic Plants 0,0012 mg/l

**CALCIUM CARBONATE** 

EC50 - for Algae / Aquatic Plants 14 mg/l/72h EC10 for Algae / Aquatic Plants 14 mg/l/72h Chronic NOEC for Algae / Aquatic Plants 14 mg/l

CALCINED KAOLIN-CAOLINO CALCINATO

 LC50 - for Fish
 100 mg/l/96h

 EC50 - for Crustacea
 100 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 2,5 mg/l/72h

 EC10 for Algae / Aquatic Plants
 41 mg/l/72h

 Chronic NOEC for Fish
 100 mg/l

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 10 / 14

Page n. 10 / 14 Replaced revision:1 (Dated 14/01/2025)

#### **SECTION 12. Ecological information** .../>>

Chronic NOEC for Crustacea 100 mg/l Chronic NOEC for Algae / Aquatic Plants 41 mg/l

MINEMA 1-2-44

 LC50 - for Fish
 > 10000 mg/l/96h

 EC50 - for Crustacea
 > 1000 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 75 mg/l/72h

#### 12.2. Persistence and degradability

3-iodo-2-propinilbutilcarbammato

Solubility in water 168 mg/l Entirely degradable 100%

Ossirano, 2-metil-,polimero con ossirano,etere con 1,2,3 propanetriolo (3:1) Entirely degradable >60%-28 Giorni

**TALC** 

Solubility in water 0,1 mg/l

Degradability: information not available Sostanza inorganica

TITANIUM DIOXIDE

Degradability: information not available Sostanza inorganica

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Solubility in water 500 mg/l

NOT rapidly degradable

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

NOT rapidly degradable <50%

**CALCIUM CARBONATE** 

Solubility in water 16,6 mg/l

Degradability: information not available Sostanza inorganica

CALCINED KAOLIN-CAOLINO CALCINATO

Solubility in water 1,15 mg/l

Degradability: information not available Sostanza inorganica

MINEMA 1-2-44

Solubility in water 14 mg/l

Degradability: information not available Sostanza inorganica

#### 12.3. Bioaccumulative potential

3-iodo-2-propinilbutilcarbammato

Partition coefficient: n-octanol/water 2,81 Log Kow

TALC

Partition coefficient: n-octanol/water -9,4 Log Kow

CF 3,16

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Partition coefficient: n-octanol/water 2,61 Log Kow BCF 19.21

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Partition coefficient: n-octanol/water < 0,71 Log Kow Metodo HPLC

BCF 3,16

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

#### ΕN

## Licata S.p.A. P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 11 / 14 Replaced revision:1 (Dated 14/01/2025)

#### SECTION 12. Ecological information .../>>

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

#### 14.2. UN proper shipping name

not applicable

#### 14.3. Transport hazard class(es)

not applicable

#### 14.4. Packing group

not applicable

#### 14.5. Environmental hazards

not applicable

#### 14.6. Special precautions for user

not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

#### **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 12 / 14 Replaced revision:1 (Dated 14/01/2025)

#### SECTION 15. Regulatory information .../>>

Product

Point 3
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2 Acute toxicity, category 2
Acute Tox. 3 Acute toxicity, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

Skin Corr. 1C
Skin Corr. 1
Skin corrosion, category 1C
Skin Corr. 1
Skin corrosion, category 1
Eye Dam. 1
Serious eye damage, category 1
Eye Irrit. 2
Skin Irrit. 2
Skin Irrit. 2
Skin Sens. 1
Skin Sens. 1
Skin sensitization, category 1
Skin sens. 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

**H310** Fatal in contact with skin.

H330 Fatal if inhaled.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H302 Harmful if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H315 Causes skin irritation.

**H317** May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

**EUH071** Corrosive to the respiratory tract.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road

### P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 13 / 14

Replaced revision:1 (Dated 14/01/2025)

#### SECTION 16. Other information .../>>

- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

## Licata S.p.A. P113752 - Sesia

Revision nr.2 Dated 05/05/2025 Printed on 05/05/2025 Page n. 14 / 14 Replaced revision:1 (Dated 14/01/2025)

#### SECTION 16. Other information .../>>

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01/03/08/09/10/11/12/16.