

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: P001009
Product name: BETONFIP TIXO F
UFI: RTX0-K01R-R007-6NXM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: repair mortar

1.3. Details of the supplier of the safety data sheet

Name: Licata S.p.A.
Full address: Via dei Mille 32
District and Country: 00185 Roma (RM)
Italia
Tel.: +39 0922 856088
Fax: +39 0922 831427
e-mail address of the competent person responsible for the Safety Data Sheet: controllo-qualita@licataspa.it

1.4. Emergency telephone number

For urgent inquiries refer to:
NHS111in England: 111
NHS24in Scotland: 111
NHS Direct in Wales: 111 or 0845 4647
In an emergency, if the patient has collapsed or is not breathing properly, call 999

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

Precautionary statements:

Contains: Portland cement clinker
flue dust
Ossido di Calcio

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0.1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq 0.1\%$.

3.2. Mixtures

Contains:

EPY 11.9.0 - SDS 1004.14

SECTION 3. Composition/information on ingredients ... / >>**STANNOUS SULFATE**

INDEX

 $0,003 \leq x < 0,006$ **Acute Tox. 4 H332, STOT RE 2 H373, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 3 H412**
LC50 Inhalation mists/powders: 2 mg/l

EC 231-302-2

CAS 7488-55-3

REACH Reg. 01-2119856668-19-0000

QUARTZ

INDEX

 $0 < x < 0,003$ **STOT RE 1 H372**

EC 238-878-4

CAS 14808-60-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

Licata S.p.A. P001009 - BETONFIP TIXO F		Revision nr.4 Dated 23/09/2025 Printed on 23/09/2025 Page n. 4 / 15 Replaced revision:3 (Dated 07/10/2024)	EN
SECTION 5. Firefighting measures ... / >>			
5.3. Advice for firefighters			
GENERAL INFORMATION			
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.			
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS			
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).			
SECTION 6. Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
If there are no contraindications, spray powder with water to prevent the formation of dust.			
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.			
6.2. Environmental precautions			
The product must not penetrate into the sewer system or come into contact with surface water or ground water.			
6.3. Methods and material for containment and cleaning up			
Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.			
Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.			
6.4. Reference to other sections			
Any information on personal protection and disposal is given in sections 8 and 13.			
SECTION 7. Handling and storage			
7.1. Precautions for safe handling			
Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.			
7.2. Conditions for safe storage, including any incompatibilities			
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.			
7.3. Specific end use(s)			
Information not available			
SECTION 8. Exposure controls/personal protection			
8.1. Control parameters			
Regulatory references:			
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe	
ESP	España	Límites de exposición profesional para agentes químicos en España 2024	
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021	
HRV	Hrvatska	PRAVILNIK O IZMJENAMA I DOPUNAMA PRAVILNIKA O ZAŠTITI RADNIKA OD IZLOŽENOSTI OPASNIM KEMIČALIJAMA NA RADU, GRANIČNIM VRIJEDNOSTIMA IZLOŽENOSTI I BIOLOŠKIM GRANIČNIM VRIJEDNOSTIMA	
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81	
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024	
			EPY 11.9.0 - SDS 1004.14

GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,37	mg/l
Normal value in marine water	0,24	mg/l
Normal value for water, intermittent release	0,37	mg/l
Normal value for fresh water, intermittent release	0,24	mg/l
Normal value of STP microorganisms	2,27	mg/l
Normal value for the terrestrial compartment	817.4	mg/kg/d

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	4 mg/m3		1 mg/m3		4 mg/m3		1 mg/m3	

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLEP	ITA	1				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,282	mg/l
Normal value in marine water	0,028	mg/l
Normal value for fresh water sediment	0,875	mg/kg/d
Normal value for marine water sediment	0,088	mg/kg/d
Normal value for water, intermittent release	0,282	mg/l
Normal value of STP microorganisms	6	mg/l
Normal value for the terrestrial compartment	5	mg/kg/d

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			0,84 mg/m3		4 mg/m3		0,84 mg/m3	

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
MV	SVN	0,05				RESP
OEL	EU	0.1				RESP

P001009 - BETONFIP TIXO F**SECTION 8. Exposure controls/personal protection ... / >>****QUARTZ****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
MV	SVN	0,15				RESP
OEL	EU	0,1				RESP

CALCIUM HYDROXIDE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1		2		INHAL
MAK	DEU	1		2		INHAL
VLA	ESP	1		4		
VLEP	FRA	1		4		
GVI/KGVI	HRV	1		4		RESP
VLEP	ITA	1		4		RESP
MV	SVN	1		4		
WEL	GBR	5				INHAL
WEL	GBR	1		4		RESP
OEL	EU	1		4		RESP

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,49	mg/l
Normal value in marine water	0,32	mg/l
Normal value for water, intermittent release	0,49	mg/l
Normal value of STP microorganisms	3	mg/l
Normal value for the terrestrial compartment	1080	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation	4		1		4		1	
	mg/m3		mg/m3		mg/m3		mg/m3	

STANNOUS SULFATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	2				Como Sn
GVI/KGVI	HRV	2				Kao Sn
VLEP	ITA	2				Sn
MV	SVN	8				INHAL Kot Sn
WEL	GBR	2		4		As Sn
OEL	EU	2				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,032	mg/l
Normal value in marine water	0,0032	mg/l
Normal value for fresh water sediment	11889	mg/kg/d
Normal value for marine water sediment	1188,9	mg/kg/d
Normal value for water, intermittent release	0,182	mg/l
Normal value of STP microorganisms	83,4	mg/l
Normal value for the terrestrial compartment	0,136	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				0,88				
				mg/kg bw/d				
Inhalation		2,41	0,046	1,53		3241	0,180	8,67
		mg/m3	mg/m3	mg/m3		mg/m3	mg/m3	mg/m3
Skin		0,88		0,88		2,46		2,46
		mg/kg bw/d		mg/kg bw/d		mg/kg bw/d		mg/kg bw/d

SECTION 8. Exposure controls/personal protection ... / >>

BENTONITE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLEP	ITA	0,1						
OEL	EU	10				INHAL		
OEL	EU	3				RESP		

Fumes, silica								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	0,1				RESP	polvere di silice cristallina	

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers		Chronic	Chronic	Effects on workers			
	Acute	Acute			Acute	Acute	Chronic	Chronic
Inhalation	local	systemic	local	systemic	local	systemic	local	systemic
							0,300	
							mg/m3	

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment. The above values are not TLVs, but guide values, to be used for particles that do not have their own TLV and that are insoluble or poorly soluble in water and have low toxicity.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.
Provide an emergency shower with face and eye wash station.

HAND PROTECTION
In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).
Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION
Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION
Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION
Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	powder	
Colour	grey	
Odour	not available	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	

P001009 - BETONFIP TIXO F**SECTION 9. Physical and chemical properties** ... / >>

Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	12	
Kinematic viscosity	not available	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	2150	g/l
Relative vapour density	not available	
Particle characteristics	not available	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

Portland cement clinker

When mixed with water, the white concrete hardens forming a stable mass that does not react with the environment.

CALCIUM CARBONATE

Decomposes at temperatures above 800°C/1472°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

QUARTZ

Stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

10.4. Conditions to avoid

Avoid environmental dust build-up.

QUARTZ

Decomposes if exposed to: sources of heat.

10.5. Incompatible materials

QUARTZ

Incompatible with: Oxidants.

CALCIUM CARBONATE

Incompatible with: acids.

CALCIUM HYDROXIDE

Incompatible with: acids, light metals, Organic nitrogen compounds, water, phosphorus, Hydrogen sulfur.

10.6. Hazardous decomposition products

CALCIUM CARBONATE

May develop: calcium oxides, carbon oxides.

Licata S.p.A.		Revision nr.4 Dated 23/09/2025 Printed on 23/09/2025 Page n. 9 / 15 Replaced revision:3 (Dated 07/10/2024)		EN
P001009 - BETONFIP TIXO F				
SECTION 11. Toxicological information				
In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.				
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008				
Metabolism, toxicokinetics, mechanism of action and other information				
Information not available				
Information on likely routes of exposure				
Information not available				
Delayed and immediate effects as well as chronic effects from short and long-term exposure				
Information not available				
Interactive effects				
Information not available				
ACUTE TOXICITY				
ATE (Inhalation) of the mixture:		Not classified (no significant component)		
ATE (Oral) of the mixture:		Not classified (no significant component)		
ATE (Dermal) of the mixture:		Not classified (no significant component)		
CALCIUM CARBONATE				
LD50 (Dermal):		2000 mg/kg Rat		
LD50 (Oral):		2000 mg/kg Rat		
LC50 (Inhalation mists/powders):		3 mg/l Rat		
Miscela complessa di silicati e alluminati di calcio				
LD50 (Dermal):		4000 mg/kg Ratto		
LD50 (Oral):		2000 mg/kg Ratto		
LC50 (Inhalation mists/powders):		5235 mg/l Ratto		
Ossido di Calcio				
LD50 (Oral):		2000 mg/kg Ratto		
LC50 (Inhalation mists/powders):		6,04 mg/l/4h Ratto		
Fumes, silica				
LD50 (Dermal):		5000 mg/kg Rabbit		
LD50 (Oral):		5000 mg/kg Rat		
LC50 (Inhalation mists/powders):		140 mg/l Rat		
flue dust				
LD50 (Dermal):		2000 mg/kg Ratto		
LD50 (Oral):		1848 mg/kg Ratto		
LC50 (Inhalation mists/powders):		6,04 mg/l/4h Ratto		
BENTONITE				
LD50 (Oral):		> 2000 mg/kg Rat		
LC50 (Inhalation mists/powders):		> 5,27 mg/l Rat		
CALCIUM HYDROXIDE				
LD50 (Dermal):		2500 mg/kg Coniglio		
LD50 (Oral):		2000 mg/kg Ratto		
LC50 (Inhalation mists/powders):		6,04 mg/l/4h Ratto		
STANNOUS SULFATE				
LD50 (Oral):		2207 mg/kg Rat		
LC50 (Inhalation mists/powders):		2 mg/l Rat		
EPY 11.9.0 - SDS 1004.14				

P001009 - BETONFIP TIXO F**SECTION 11. Toxicological information ... / >>**SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity**CALCIUM CARBONATE**

EC50 - for Algae / Aquatic Plants 14 mg/l/72h

EC10 for Algae / Aquatic Plants 14 mg/l/72h

Chronic NOEC for Algae / Aquatic Plants 14 mg/l

Miscela complessa di silicati e alluminati di calcio

LC50 - for Fish 550000 mg/l/96h

EC50 - for Crustacea 506500 mg/l/48h

EC50 - for Algae / Aquatic Plants 80000 mg/l/72h

EC10 for Algae / Aquatic Plants 32000 mg/l/72h

Chronic NOEC for Fish 500000 mg/l 6 mesi

Chronic NOEC for Crustacea 50000 mg/l

Chronic NOEC for Algae / Aquatic Plants 32000 mg/l

Ossido di Calcio

LC50 - for Fish 50,6 mg/l/96h

EC50 - for Crustacea 49,1 mg/l/48h

EC50 - for Algae / Aquatic Plants 184,57 mg/l/72h

EC10 for Crustacea 75 mg/l/48h

EC10 for Algae / Aquatic Plants 79,22 mg/l/72h

Chronic NOEC for Crustacea 33,3 mg/l

P001009 - BETONFIP TIXO F

SECTION 12. Ecological information ... / >>

Chronic NOEC for Algae / Aquatic Plants	48 mg/l
Fumes, silica	
LC50 - for Fish	100 mg/l/96h
EC50 - for Algae / Aquatic Plants	250 mg/l/72h
LC10 for Fish	10000 mg/l/96h
EC10 for Algae / Aquatic Plants	228 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	228 mg/l
flue dust	
EC50 - for Algae / Aquatic Plants	28,2 mg/l/72h
EC10 for Algae / Aquatic Plants	10,3 mg/l/72h
Chronic NOEC for Fish	11,1 mg/l
Chronic NOEC for Crustacea	100 mg/l
Chronic NOEC for Algae / Aquatic Plants	10,3 mg/l
BENTONITE	
LC50 - for Fish	16000 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
CALCIUM HYDROXIDE	
LC50 - for Fish	50,6 mg/l/96h
EC50 - for Crustacea	49,1 mg/l/48h
EC50 - for Algae / Aquatic Plants	184,57 mg/l/72h
EC10 for Crustacea	75 mg/l/48h
EC10 for Algae / Aquatic Plants	79,22 mg/l/72h
Chronic NOEC for Fish	32 mg/l
Chronic NOEC for Crustacea	33,3 mg/l
Chronic NOEC for Algae / Aquatic Plants	48 mg/l
STANNOUS SULFATE	
LC50 - for Fish	29,5 mg/l/96h
EC50 - for Crustacea	55 mg/l/48h
EC50 - for Algae / Aquatic Plants	18,2 mg/l/72h
EC10 for Algae / Aquatic Plants	9,1 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	9,1 mg/l

12.2. Persistence and degradability

CALCIUM CARBONATE	
Solubility in water	16,6 mg/l
Degradability: information not available	Sostanza inorganica
Portland cement clinker	
Solubility in water	800 mg/l
Degradability: information not available	Sostanza inorganica
QUARTZ	
Degradability: information not available	
Miscela complessa di silicati e alluminati di calcio	
Solubility in water	0,01 mg/l
NOT rapidly degradable	
Ossido di Calcio	
Solubility in water	1338 mg/l
Degradability: information not available	Sostanza Inorganica
Fumes, silica	
Solubility in water	135 mg/l
Degradability: information not available	Sostanza inorganica
flue dust	
Degradability: information not available	

Licata S.p.A. P001009 - BETONFIP TIXO F		Revision nr.4 Dated 23/09/2025 Printed on 23/09/2025 Page n. 12 / 15 Replaced revision:3 (Dated 07/10/2024)	EN
SECTION 12. Ecological information ... / >>			
BENTONITE			
Degradability: information not available		Sostanza inorganica	
CALCIUM HYDROXIDE			
Solubility in water		1845 mg/l	
Degradability: information not available		Sostanza inorganica	
STANNOUS SULFATE			
Solubility in water		188000 mg/l	
Rapidly degradable			
QUARTZ			
Degradability: information not available			
12.3. Bioaccumulative potential			
Miscela complessa di silicati e alluminati di calcio			
Partition coefficient: n-octanol/water		-9 Log Kow	
BCF		10	
STANNOUS SULFATE			
BCF		3000	
12.4. Mobility in soil			
STANNOUS SULFATE			
Partition coefficient: soil/water		371535,229	
12.5. Results of PBT and vPvB assessment			
On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.			
12.6. Endocrine disrupting properties			
Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.			
12.7. Other adverse effects			
Information not available			
SECTION 13. Disposal considerations			
13.1. Waste treatment methods			
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.			
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.			
The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.			
CONTAMINATED PACKAGING			
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.			
SECTION 14. Transport information			
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.			
14.1. UN number or ID number			
not applicable			
EPY 11.9.0 - SDS 1004.14			

P001009 - BETONFIP TIXO F

SECTION 14. Transport information ... / >>

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: NoneRestrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Contained substance
Point 75Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicableSubstances in Candidate List (Art. 59 REACH)
On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.Substances subject to authorisation (Annex XIV REACH)
NoneSubstances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
NoneSubstances subject to the Rotterdam Convention:
NoneSubstances subject to the Stockholm Convention:
NoneHealthcare controls
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

SECTION 16. Other information ... / >>

11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 16.