#### F١

# Licata S.p.A. P10903 - BETONFIP TIXO

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 1 / 14

Replaced revision:4 (Dated 07/10/2024)

# **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **P10903** 

Product name BETONFIP TIXO

UFI: QQX0-20CC-E00R-JACJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use repair mortar

1.3. Details of the supplier of the safety data sheet

Name Licata S.p.A.
Full address Via dei Mille 32

District and Country 00185 Roma (RM)

Italia

Tel. +39 0922 856088 Fax +39 0922 831427

e-mail address of the competent person

responsible for the Safety Data Sheet controllo-qualita@licataspa.it

1.4. Emergency telephone number

For urgent inquiries refer to NHS111in England: 111

NHS24in Scotland: 111

NHS Direct in Wales: 111 or 0845 4647

In an emergency, if the patient has collapsed or is not breathing properly, call 999

### **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 Causes serious eye damage.
Skin irritation, category 2 H315 Causes skin irritation.
Specific target organ toxicity - single exposure, H335 May cause respiratory irritation.

category 3

Skin sensitization, category 1 H317 May cause an allergic skin reaction.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Printed on 23/09/2025 Page n. 2 / 14

Replaced revision:4 (Dated 07/10/2024)

#### SECTION 2. Hazards identification .../>>

Hazard statements:

H318 Causes serious eye damage. H315 Causes skin irritation.

H335 May cause respiratory irritation. H317 May cause an allergic skin reaction.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P280 Wear protective gloves / eye protection / face protection. P310 Immediately call a POISON CENTER / doctor / . . P261 Avoid breathing dust / fume / gas / mist / vapours / spray. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P264 Wash . . . thoroughly after handling.

Contains: Portland cement clinker

> flue dust Ossido di Calcio

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

# **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Identification x = Conc. %Classification (EC) 1272/2008 (CLP)

Portland cement clinker

INDEX  $21 \le x < 22,5$ Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317

266-043-4 FC CAS 65997-15-1

REACH Reg. 02-2119682167-31-0000

QUARTZ

INDEX  $19,5 \le x < 21$ Substance with a community workplace exposure limit.

238-878-4 EC CAS 14808-60-7

Ossido di Calcio

INDEX Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335  $1 \le x < 2$ 

EC 215-138-9 CAS 1305-78-8

Fumes, silica

Substance with a community workplace exposure limit. INDEX  $1 \le x < 2$ 

273-761-1 EC CAS 69012-64-2

REACH Reg. 01-2119486866-17-0001

flue dust

Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317 INDEX  $1 \le x < 2$ 

EC 270-659-9 CAS 68475-76-3

REACH Reg. 01-2119486767-17-0xxx

BENTONITE

CAS

INDEX  $0.5 \le x < 0.8$ Substance with a community workplace exposure limit.

FC 215-108-5 CAS 1302-78-9

STANNOUS SULFATE

Acute Tox. 4 H332, STOT RE 2 H373, Eye Dam. 1 H318, Skin Irrit. 2 H315, **INDEX** 0 < x < 0.003

STOT SE 3 H335, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 231-302-2 LC50 Inhalation mists/powders: 2 mg/l

7488-55-3 REACH Reg. 01-2119856668-19-0000

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 3 / 14

Replaced revision:4 (Dated 07/10/2024)

#### SECTION 3. Composition/information on ingredients .../>

**QUARTZ** 

INDEX 0 < x < 0,003 STOT RE 1 H372

EC 238-878-4 CAS 14808-60-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

#### Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

# 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 4 / 14

Replaced revision:4 (Dated 07/10/2024)

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

If there are no contraindications, spray powder with water to prevent the formation of dust.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Evaluate the compatibility of the container to be used, by checking section 10. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

# 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

#### SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory references:

ESP España Límites de exposición profesional para agentes químicos en España 2024

FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849

du 28 décembre 2021

HRV Hrvatska PRAVILNIK O IZMJENAMA I DOPUNAMA PRAVILNIKA O ZAŠTITI RADNIKA OD

IZLOŽENOSTI OPASNIM KEMIKALIJAMA NA RADU, GRANIČNIM VRIJEDNOSTIMA

IZLOŽENOSTI I BIOLOŠKIM GRANIČNIM VRIJEDNOSTIMA

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

SVN Slovenija Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali

reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

FU OFL FU Directive (EU) 2022/431: Directive (EU) 2019/1831: Directive

OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 5 / 14 Replaced revision:4 (Dated 07/10/2024)

# SECTION 8. Exposure controls/personal protection

Ossido di Calcio								
Predicted no-effect cor	ncentration	- PNEC						
Normal value in fresh water 0,37 mg/l								
Normal value in marir	ne water					0,24	mg/l	
Normal value for water	er, intermitte	nt release				0,37	mg/l	
Normal value for fres	h water, inte	rmittent release				0,24	mg/l	
Normal value of STP	microorgani	sms				2,27	mg/l	
Normal value for the	terrestrial co	mpartment				817,4	mg/kg/d	
Health - Derived no-effe	ect level - D	NEL / DMEL						
	Effects or	n consumers			Effects on v	workers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation	4		1		4		1	
	mg/m3		mg/m3		mg/m3		mg/m3	

Portland cement clinker							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLEP	ITA	1					

			f	ue dust				
Predicted no-effect cor	ncentration	- PNEC	••	uc uust				
Normal value in fresh	0,282	mg/l						
Normal value in mari	ne water					0,028	mg/l	
Normal value for fres	h water sed	iment				0,875	mg/kg/d	
Normal value for mar	ine water se	ediment				0,088	mg/kg/d	
Normal value for water	er, intermitte	ent release				0,282	mg/l	
Normal value of STP	microorgan	isms				6	mg/l	
Normal value for the	terrestrial co	mpartment				5	mg/kg/d	
Health - Derived no-eff	ect level - C	NEL / DMEL						
	Effects o	n consumers			Effects on w	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation			0,84 mg/m3		4 mg/m3		0,84 mg/m3	

				QUARTZ		
<b>Threshold Limit</b>	t Value					
Туре	Country	TWA/8h		STEL/15mir	1	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
GVI/KGVI	HRV	0,1				
VLEP	ITA	0,1				RESP
MV	SVN	0,05				RESP
OEL	EU	0,1				RESP

				QUARTZ					
Threshold Limit Value									
Туре	Country	TWA/8h		STEL/15mir	า	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
VLA	ESP		0,05			RESP			
VLEP	FRA	0,1				RESP			
GVI/KGVI	HRV	0,1							
VLEP	ITA	0,1				RESP			
MV	SVN	0,15				RESP			
OEL	EU	0,1				RESP			

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 6 / 14

Replaced revision:4 (Dated 07/10/2024)

### SECTION 8. Exposure controls/personal protection .../>

			;	STANNOU	S SULFATE					
hreshold Limit V	alue									
Туре	Country	TWA/8h		STE	L/15min		Remarl	ks / Observa	tions	
		mg/m3	ppm	mg/ı	m3	opm				
VLA	ESP	2						Como Sn		
GVI/KGVI	HRV	2						Kao Sn		
VLEP	ITA	2						Sn		
MV	SVN	8					INHAL	Kot Sn		
WEL	GBR	2		4				As Sn		
OEL	EU	2								
redicted no-effect	t concentra	ation - PNEC								
Normal value in	fresh water							0,032	mg/l	
Normal value in	marine water	er						0,0032	mg/l	
Normal value fo	r fresh wate	r sediment						11889	mg/kg/d	
Normal value fo	r marine wa	ter sediment						1188,9	mg/kg/d	
Normal value fo	r water, inte	rmittent release						0,182	mg/l	
Normal value of	STP micro	organisms						83,4	mg/l	
Normal value fo	r the terresti	rial compartment	<u> </u>					0,136	mg/kg/d	
ealth - Derived n	o-effect lev	el - DNEL / DME	EL							
	Effe	cts on consumer	rs			Effects	on worke	rs		
Route of exposu	ıre Acu	te Acute	Ch	ronic	Chronic	Acute		Acute	Chronic	Chronic
	loca	ıl system	ic loc	al	systemic	local		systemic	local	systemic
Oral					0,88					
					mg/kg bw/d					
Inhalation		2,41	0,0	46	1,53			3241	0,180	8,67
		mg/m3	mg	/m3	mg/m3			mg/m3	mg/m3	mg/m3
Skin		0,88			0,88			2,46		2,46
		mg/kg l	ow/d		mg/kg bw/d			mg/kg		mg/kg
								bw/d		bw/d

				BENTONITE				
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLEP	ITA	0,1						
OEL	EU	10				INHAL		
OEL	EU	3				RESP		

					Fu	mes, silica					
Threshold Lim	it Value										
Type	Cou	ntry T	WA/8h		;	STEL/15min		Remark	ks / Observa	ations	
		n	ng/m3	ppm	ı	mg/m3	ppm				
OEL	EU		0,1			_		RESP	polvere di	silice cristalli	na
Health - Derive	d no-effe	ect level -	<b>DNEL / DME</b>	L							
		Effects	on consumers	3			Effects	on worke	rs		
Route of exp	osure	Acute	Acute		Chronic	Chronic	Acute		Acute	Chronic	Chronic
		local	systemi	2	local	systemic	local		systemic	local	systemic
Inhalation						•			•	0,300	•
										mg/m3	

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment. The above values are not TLVs, but guide values, to be used for particles that do not have their own TLV and that are insoluble or poorly soluble in water and have low toxicity.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### ΕN

# Licata S.p.A. P10903 - BETONFIP TIXO

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 7 / 14

Information

Replaced revision:4 (Dated 07/10/2024)

#### SECTION 8. Exposure controls/personal protection .../>>

#### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374). Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

**ENVIRONMENTAL EXPOSURE CONTROLS** 

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Properties	Value
Appearance	powder
Colour	grey
Odour	not available
Melting point / freezing point	not available
Initial boiling point	not available
Flammability	not available
Lower explosive limit	not available
Upper explosive limit	not available
Flash point	not available
Auto-ignition temperature	not available
Decomposition temperature	not available
рН	12
Kinematic viscosity	not available
Solubility	not available
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	not available
Relative vapour density	not available
Particle characteristics	not available

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

## **SECTION 10. Stability and reactivity**

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Portland cement clinker

When mixed with water, the white concrete hardens forming a stable mass that does not react with the environment.

#### **CALCIUM CARBONATE**

Decomposes at temperatures above 800°C/1472°F.

EPY 11.9.0 - SDS 1004.14

Dated 23/09/2025 Printed on 23/09/2025 Page n. 8 / 14

Replaced revision:4 (Dated 07/10/2024)

### SECTION 10. Stability and reactivity .../>>

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

QUARTZ

Stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

#### 10.4. Conditions to avoid

Avoid environmental dust build-up.

QUART7

Decomposes if exposed to: sources of heat.

#### 10.5. Incompatible materials

QUARTZ

Incompatible with: Oxidants.
CALCIUM CARBONATE
Incompatible with: acids.

#### 10.6. Hazardous decomposition products

**CALCIUM CARBONATE** 

May develop: calcium oxides, carbon oxides.

### **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

**CALCIUM CARBONATE** 

 LD50 (Dermal):
 2000 mg/kg Rat

 LD50 (Oral):
 2000 mg/kg Rat

 LC50 (Inhalation mists/powders):
 3 mg/l Rat

Miscela complessa di silicati e alluminati di calcio

LD50 (Dermal):4000 mg/kg RattoLD50 (Oral):2000 mg/kg RattoLC50 (Inhalation mists/powders):5235 mg/l Ratto

Dated 23/09/2025
Printed on 23/09/2025
Page n. 9 / 14
Replaced revision:4 (Dated 07/10/2024)

#### **SECTION 11. Toxicological information** .../>>

Ossido di Calcio

LD50 (Oral): 2000 mg/kg Ratto LC50 (Inhalation mists/powders): 6,04 mg/l/4h Ratto

Fumes, silica

LD50 (Dermal): 5000 mg/kg Rabbit LD50 (Oral): 5000 mg/kg Rat LC50 (Inhalation mists/powders): 140 mg/l Rat

flue dust

LD50 (Dermal): 2000 mg/kg Ratto LD50 (Oral): 1848 mg/kg Ratto LC50 (Inhalation mists/powders): 6,04 mg/l/4h Ratto

BENTONITE

LD50 (Oral): > 2000 mg/kg Rat LC50 (Inhalation mists/powders): > 5,27 mg/l Rat

STANNOUS SULFATE

LD50 (Oral): 2207 mg/kg Rat LC50 (Inhalation mists/powders): 2 mg/l Rat

#### SKIN CORROSION / IRRITATION

Causes skin irritation

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause respiratory irritation

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 10 / 14

Replaced revision:4 (Dated 07/10/2024)

#### SECTION 12. Ecological information .../>>

**CALCIUM CARBONATE** 

EC50 - for Algae / Aquatic Plants 14 mg/l/72h EC10 for Algae / Aquatic Plants 14 mg/l/72h Chronic NOEC for Algae / Aquatic Plants 14 mg/l

Miscela complessa di silicati e alluminati di calcio

 LC50 - for Fish
 550000 mg/l/96h

 EC50 - for Crustacea
 506500 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 80000 mg/l/72h

 EC10 for Algae / Aquatic Plants
 32000 mg/l/72h

 Chronic NOEC for Fish
 500000 mg/l 6 mesi

 Chronic NOEC for Crustacea
 50000 mg/l

 Chronic NOEC for Algae / Aquatic Plants
 32000 mg/l

Ossido di Calcio

 LC50 - for Fish
 50,6 mg/l/96h

 EC50 - for Crustacea
 49,1 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 184,57 mg/l/72h

 EC10 for Crustacea
 75 mg/l/48h

 EC10 for Algae / Aquatic Plants
 79,22 mg/l/72h

 Chronic NOEC for Crustacea
 33,3 mg/l

 Chronic NOEC for Algae / Aquatic Plants
 48 mg/l

Fumes, silica

 LC50 - for Fish
 100 mg/l/96h

 EC50 - for Algae / Aquatic Plants
 250 mg/l/72h

 LC10 for Fish
 10000 mg/l/96h

 EC10 for Algae / Aquatic Plants
 228 mg/l/72h

 Chronic NOEC for Algae / Aquatic Plants
 228 mg/l

flue dust

EC50 - for Algae / Aquatic Plants 28,2 mg/l/72h
EC10 for Algae / Aquatic Plants 10,3 mg/l/72h
Chronic NOEC for Fish 11,1 mg/l
Chronic NOEC for Crustacea 100 mg/l
Chronic NOEC for Algae / Aquatic Plants 10,3 mg/l

**BENTONITE** 

 LC50 - for Fish
 16000 mg/l/96h

 EC50 - for Crustacea
 > 100 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

STANNOUS SULFATE

 LC50 - for Fish
 29,5 mg/l/96h

 EC50 - for Crustacea
 55 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 18,2 mg/l/72h

 EC10 for Algae / Aquatic Plants
 9,1 mg/l/72h

 Chronic NOEC for Algae / Aquatic Plants
 9,1 mg/l

#### 12.2. Persistence and degradability

**CALCIUM CARBONATE** 

Solubility in water 16,6 mg/l

Degradability: information not available Sostanza inorganica

Portland cement clinker

Solubility in water 800 mg/l

Degradability: information not available Sostanza inorganica

QUARTZ

Degradability: information not available

Miscela complessa di silicati e alluminati di calcio

Solubility in water 0,01 mg/l

NOT rapidly degradable

#### ΕN

# Licata S.p.A. P10903 - BETONFIP TIXO

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 11 / 14

Replaced revision:4 (Dated 07/10/2024)

#### SECTION 12. Ecological information .../>>

Ossido di Calcio

Solubility in water 1338 mg/l

Degradability: information not available Sostanza Inorganica

Fumes, silica

Solubility in water 135 mg/l

Degradability: information not available Sostanza inorganica

flue dust

Degradability: information not available

**BENTONITE** 

Degradability: information not available Sostanza inorganica

STANNOUS SULFATE

Solubility in water 188000 mg/l

Rapidly degradable

QUARTZ

Degradability: information not available

#### 12.3. Bioaccumulative potential

Miscela complessa di silicati e alluminati di calcio

Partition coefficient: n-octanol/water -9 Log Kow

F .

STANNOUS SULFATE

BCF 3000

#### 12.4. Mobility in soil

STANNOUS SULFATE

Partition coefficient: soil/water 371535,229

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### ΕN

# Licata S.p.A. P10903 - BETONFIP TIXO

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 12 / 14 Replaced revision:4 (Dated 07/10/2024)

SECTION 14. T	Fransport information/>>
---------------	--------------------------

not applicable

14.2. UN proper shipping name

14.1. UN number or ID number

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

## **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 13 / 14

Replaced revision:4 (Dated 07/10/2024)

#### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1 Specific target organ toxicity - repeated exposure, category 2 STOT RE 2

Eve Dam. 1 Serious eye damage, category 1 Skin irritation, category 2 Skin Irrit. 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin sensitization, category 1 Skin Sens. 1 Skin Sens. 1B Skin sensitization, category 1B

**Aquatic Chronic 3** Hazardous to the aquatic environment, chronic toxicity, category 3

H332 Harmful if inhaled.

Causes damage to organs through prolonged or repeated exposure. H372 H373 May cause damage to organs through prolonged or repeated exposure.

H318 Causes serious eye damage. H315 Causes skin irritation.

May cause respiratory irritation. H335 H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

Revision nr.5 Dated 23/09/2025 Printed on 23/09/2025 Page n. 14 / 14 Replaced revision:4 (Dated 07/10/2024)

#### SECTION 16. Other information .../>>

- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 10 / 11 / 12 / 13 / 16.